

Customer: Audio Research Corporation
 Model Number: REF 6 PREAMP (Program Code = 17)
 Casing: SC-29
 Carrier Frequency: 38KHz
 Protocol: Philips RC5
 System Code: Complete R5 code=1+1+T+device code+command code(see data code below)
 Where T toggles each time a transmission starts
 Device Code: 00111(b)
 Repeat Code:

10/30/07 Revision

Key Number	Key Name	Hex Code	Dec Code	Data Code					
				D5	D4	D3	D2	D1	D0
1	HOURS	0	0	0	0	0	0	0	0
2	POWER	1	1	0	0	0	0	0	1
3	BAL 1	2	2	0	0	0	0	1	0
4	BAL 2	3	3	0	0	0	0	1	1
5	BAL 3	4	4	0	0	0	1	0	0
6	BAL 4	5	5	0	0	0	1	0	1
7	SE 1	6	6	0	0	0	1	1	0
8	SE 2	7	7	0	0	0	1	1	1
9	SE 3	8	8	0	0	1	0	0	0
10	-	9	9	0	0	1	0	0	1
11	SE4	A	10	0	0	1	0	1	0
12	BALANCE-L	B	11	0	0	1	0	1	1
13	-	C	12	0	0	1	1	0	0
14	BALANCE-R	D	13	0	0	1	1	0	1
15	-	E	14	0	0	1	1	1	0
16	-	F	15	0	0	1	1	1	1
17	-	10	16	0	1	0	0	0	0
18	VOLUME DN	11	17	0	1	0	0	0	1
19	MUTE	12	18	0	1	0	0	1	0
20	VOLUME UP	13	19	0	1	0	0	1	1
21	MENU	14	20	0	1	0	1	0	0
22	-	15	21	0	1	0	1	0	1
23	ENTER	16	22	0	1	0	1	1	0
24	DISPLAY DN	17	23	0	1	0	1	1	1
25	-	18	24	0	1	1	0	0	0
26	DISPLAY UP	19	25	0	1	1	0	0	1
27	INVERT	1A	26	0	1	1	0	1	0
28	-	1B	27	0	1	1	0	1	1
29	MONO	1C	28	0	1	1	1	0	0



Application Notes: This data code set is one of 20 used to support various models of remote Corporation. Each codeset can be selected via a combination of key presses as defined in the SC-29 Code Selection.doc document.