

Reference 75 SE

Stereo Amplifier



Winner of numerous awards, the Reference 75 SE is a stunning amplifier in every way – performance, styling and reliability combined to elevate your music listening to a new experience. Capable of controlling a wide variety of speakers, the Reference 75 SE will transport you into the musical performance unlike any other comparable amplifier.

At the heart of the Reference 75 SE is decades of proven Audio Research vacuum tube technology, a legacy unrivaled by any other manufacturer of tube electronics. Developed through hundreds of hours of critical listening, the carefully selected components comprising the Reference 75 SE combine to provide an amplifier which transcends traditional hi-fi, instead relaying music with realism and tangibility.

Visually, the Reference 75 SE harkens back to past Audio Research products, taking inspiration from earlier amplifier designs. With its two large VU meters, which display power output as well as provide bias adjustments, the Reference 75 SE has a timeless appearance resembling precision laboratory equipment and an overbuilt, industrious aesthetic. Offered in both natural aluminum and black finishes, the understated look will complement any system.



Specifications

Power Output: 75 watts per channel continuous from 20Hz to 20kHz. 1kHz total harmonic distortion typically 0.6% at 75 watts, below 0.05% at 1 watt. Approximate actual power available at 'clipping' 76 watts (1kHz). (Note that actual power output is dependent upon both line voltage and 'condition' i. e.: if power line has high distortion, maximum power will be affected adversely, although from a listening standpoint this is not very critical)

Power Bandwidth: (-3dB points)
7Hz to 60kHz

Frequency Response: (-3dB points
at 1 watt) 0.7Hz to 75 kHz

Input Sensitivity: 1.4V RMS BAL for rated output. (25 dB Bal gain into 8 ohms)

Input Impedance: 300K ohms Balanced

Output Polarity: Non-inverting.
Balanced input pin 2+ (IEC-268)

Output Taps: 8 ohms, 4 ohms

Output Regulation: Approximately 1.0dB 8 ohm load to open circuit (Damping factor approximately 8)

Overall Negative Feedback: 15dB

Slew Rate: 10 volts/microsecond

Rise Time: 4.0 microseconds

Hum & Noise: Less than 0.06mV RMS - 112dB below rated output (IHF weighted, input shorted)

Power Supply Energy Storage: Approximately 520 joules

Power Requirements: 105-125VAC 60Hz (210-250VAC 50Hz)
410 watts at rated output, 500 watts maximum, 230 watts idle

Tubes Required:

- 2 - Matched pair KT150 - Power Output
- 2 - 6H30 Driver

Dimensions:

- width 19" (48.3 cm)
- height 8.75" (22.2 cm)
- depth 19.5" (49.5 cm)

Handles extend 1.5" (3.8 cm) forward

Weight:

- 47 lbs. (21.3 kg) Net
- 63 lbs. (28.6 kg) Shipping